

# 4X4 Off-Road Water Bowser

## Summary

- Water Bowser
- 18T GVW.
- 5000-litre water capacity.
- M.A.N 4x4 chassis.
- 3-person safety Day Cab.

## Chassis Specification

- M.A.N TGM 18.320 4x4.
- 3900mm wheelbase – various wheelbase options available.
- M.A.N single cab (day cab), painted to customer specification.
- Full spring suspension – air options available.
- Engine D0836LFL85 - 320 hp / 235 kW EURO 6 SCR - 1250 NM C-R OBD-C without torque reduction, exemption certificate required. (options available).
- M.A.N Tipmatic gearbox.
- Power take-off on flywheel side with, 600 Nm continuous load for “pump and roll” facility.
- MI 395/85R20 XZL TL 168K all-round.

## Body Specification

- Emergency One Polypropylene Copolymer bodywork – bespoke design to meet customer requirements.
- Integrated 5000 litre water tank – capacity to customer specification (fully integral foam tank option available).
- Stowage to suit customer specification – options can be obtained on request.
- Increased departure angle for 4x4 capabilities with storage compartment below rear floor.

## Accessories

- Emergency One standard wiring harness installation and software control system integration.
- Godiva Prima 2010 pump installation (2000 litres per minute). 3010 & 4010 options available.
- 24V lighting mast c/w 2 or 4 way LED lighting. Position optional.
- All beams and ladder to customer specification – auto gantry option now available.
- Full cab protection roll cage.
- Four Cone Spray suppression Nozzles fitted to underside of front bumper.
- Emergency One’s “ePumpControl”, In-cab “eCabControl” monitor & e1fleet™ Data Logger options available.
- Front mounted T-Max DC5000 Pro 24V 5000KG Winch.
- Roof mounted water monitor, with in-cab remote joystick control facility.
- Pump and roll facility.

