

Pumping Appliance

Summary

- 2500-litre water tank capacity.
- Scania CP28 P360 4x2 chassis.
- 4.35m wheelbase.
- 2 + 3 clean cab setup

Chassis Specification

- 4.35m wheelbase.
- Front spring suspension and rear air suspension.
- 18t Gross vehicle weight.
- All crew cab glass is tinted, laminated and fitted with protective film on the full inside surface.

Body Specification

- Poly Propylene copolymer bodywork.
- 2500-litre Integrated water tank.
- Two hose reels.
- Automatic roller guides.
- Godiva 3010 pump located at the rear.
- Custom stowage solutions for a range of equipment.
- Pump bay "barn" style doors.
- Electric shutter door locking system.
- Powered Beam Gantry for main ladder and roof ladder.
- Manual pull-out step ladder under the pump bay for access to the compartment above the pump bay.
- Locker stowage for breathing apparatus.
- Three stowage lockers fitted in the crew cab for PPE and personal welfare equipment.
- All cab linings are wipeable to assist with cab cleaning and the removal of contaminants.

Accessories

- New Generation eCabControl system with 7" touchscreen mounted on the dash.
- ePumpControl system with screen.
- Each step has a white LED light that operates when accessing the vehicle.
- e1Fleet™ vehicle telematics system.
- Hygiene station located in the offside front locker on tilt and slide shelving.
- Four CCTV cameras – 1 x dash-mounted camera with internal microphone, 1 x rear camera with infrared, 2 x side (rear facing) cameras with infrared.
- Flush-mounted LED tank level indicators installed on N/S & O/S bodywork.



DATA- 152A

Further Options available.
To discuss, please contact Emergency One:
Tel : 01290 424200
Email : info@emergencyone.co.uk